

Wels, December 21st 2015

OVERSIZING FRONIUS PRIMO 3.8-1 208-240 – 15.0-1 208-240

Fronius International GmbH

hereby confirms that the inverters

- | | |
|--------------------------------------|---------------------------------------|
| / Fronius Primo 3.8-1 208-240 | / Fronius Primo 10.0-1 208-240 |
| / Fronius Primo 5.0-1 208-240 | / Fronius Primo 11.4-1 208-240 |
| / Fronius Primo 6.0-1 208-240 | / Fronius Primo 12.5-1 208-240 |
| / Fronius Primo 7.6-1 208-240 | / Fronius Primo 15.0-1 208-240 |
| / Fronius Primo 8.2-1 208-240 | |

can be oversized 50% above the rated nameplate capacity without voiding the manufacturer's warranty, provided that

- / String configuration adheres to the voltage and current window guidelines published in the operation manual
- / The open circuit voltage of the PV generator does not exceed the maximum input voltage of the inverter under any circumstances (temperature, irradiance)
- / The maximum DC array short circuit current must not exceed 1,5 times the maximum DC input current of the inverter

Fronius International GmbH

Solar Energy Division

Froniusplatz 1

A-4600 Wels



DI Thomas Mühlberger

Head of Solution Management